

AT&T FiberLine

Fiber Optic LC/UPC Duplex Multimode Uniboot Cords

Description

This page shows some of the available combinations of AT&T fiber-optic Duplex Multimode Uniboot made with multimode fibers and terminated with LC/UPC connectors. Polarity switch is enabled.

Additional combinations can be selected using the information on page B.3.

Fiber type	Select a multimode fiber from page B.6.
Buffer type	None
Strength elements	Served aramid and glass yarn
Minicable jacket material	Flame retardant LSOH compound

Standard & EU Directives Conformance

- Relevant sections of ANSI/TIA-568-C.3
- Relevant sections of ISO/IEC 11801
- Relevant sections of EN 50173
- Relevant sections of ANSI/TIA/EIA-604 (FOCIS)
- Relevant sections of IEC 60874
- Relevant sections of IEC 61753
- Relevant sections of IEC 61754
- IEC 60332-1 flame test
- IEC 60754 & IEC 61034
- EU Directive 2011/65/EU (RoHS-2)

Mechanical Properties

Short term bend radius	20xOD mm
Long term bend radius	10xOD mm
Operating temperature	-20 to +70C
	MM OM1 & OM2: Orange
Default jacket color	MM OM3: Turquoise
	MM OM4: Purple



Optional Transmission Properties

Suffix	Connector IL (dB)	Connector RL (dB)
T = Standard Loss connector	0.30 max. 0.20 Typical	20 min.
S = Low-Loss connector	0.15 max. 0.10 Typical	20 min.
L = Super Low-Loss connector	0.10 max. 0.07 Typical	20 min.

Ordering Information

FF: Fiber Type CC: Jacket Color

Description	Length m	Cable OD mm	Packaging	P/N
LC/UPC-LC/UPC Duplex Multimode Uniboot Cord LSOH	1	2.0	1/Bag - 12/Box	28UFFPP010T-CC61
LC/UPC-LC/UPC Duplex Multimode Uniboot Cord LSOH	2	2.0	1/Bag - 12/Box	28UFFPP020T-CC61
LC/UPC-LC/UPC Duplex Multimode Uniboot Cord LSOH	3	2.0	1/Bag - 12/Box	28UFFPP030T-CC61
LC/UPC-LC/UPC Duplex Multimode Uniboot Cord LSOH	5	2.0	1/Bag - 12/Box	28UFFPP050T-CC61
LC/UPC-LC/UPC Duplex Multimode Uniboot Cord LSOH	10	2.0	1/Bag - 12/Box	28UFFPP100T-CC61