

# RFP LC Uniboot to RFP LC Uniboot Patch cord, 2 fibres, Interconnect tight-buffered cable, LSZH

50 µm ClearCurve® multimode OM3, Low-Loss, 2 m

CORNING

Pretium EDGE® Solutions jumpers are integrated reverse-polarity uniboot duplex assemblies that meet the high-density space requirements of the MDA and EDA and provide a 50-percent reduction in bulk cabling when compared to traditional duplex jumpers. The highly flexible, 2-fibre interconnect cable reduces cable congestion, improves jumper management and routing and improves air circulation.

## Features and Benefits

### **Slim round 2-fibre interconnect cable, Uniboot style duplex connectors**

Improve handling in high-density applications

### **Low loss connectivity**

Enables system design flexibility

### **High performance by bend-insensitive ClearCurve® multimode or SMF-28 XB single-mode fibres**

Designed to withstand tight bends and challenging cable routes

### **LC duplex Uniboot connector design**

With changeable polarity option

### **Interchangeable Triggers**

Available in 10 different colours



## Standards

**Intermateability** TIA/EIA-6 4-10A604-10 / IEC 61754-20

## Specifications

General Specifications	
Flame Rating	LSZH™/FRNC
Cable Assembly Type	Two Fibre
Fibre Category	50 µm MM (OM3)

# RFP LC Uniboot to RFP LC Uniboot Patch cord, 2 fibres, Interconnect tight-buffered cable, LSZH

50 µm ClearCurve® multimode OM3, Low-Loss, 2 m

CORNING

## Temperature Range

Operation	-20 °C to 60 °C
Installation and Assembly	-5 °C to 50 °C
Storage	-25 °C to 70 °C

## Design - Connector A

Connector Type	LC Uniboot
Ferrule Material	Ceramic
Polish	PC
Housing Material	Composite
Housing Colour	black
Boot Type	Uniboot
Boot Colour	Turquoise
Keyed (security)	No

## Mechanical Specifications - Connector A

Durability	≤ 0.2 dB 500 rematings, FOTP-21
Tensile strength jacketed cable	44 N

## Optical Specifications - Connector A

Insertion Loss, Typical	0.1 dB
Insertion loss, max.	0.15 dB

## Design - Connector B

Connector Type	LC Uniboot
Ferrule Material	Ceramic
Polish	PC
Housing Material	Composite
Housing Colour	black
Boot Type	Uniboot
Boot Colour	Turquoise
Keyed (security)	No

# RFP LC Uniboot to RFP LC Uniboot Patch cord, 2 fibres, Interconnect tight-buffered cable, LSZH

50 µm ClearCurve® multimode OM3, Low-Loss, 2 m

CORNING

## Mechanical Specifications - Connector B

Durability	≤ 0.2 dB 500 rematings, FOTP-21
Tensile strength jacketed cable	44 N

## Optical Specifications - Connector B

Insertion Loss, Typical	0.1 dB
Insertion loss, max.	0.15 dB

## Cable Design

Fibre Count	2
Outer diameter	2 mm
Outer Jacket Colour	Turquoise
Outer Jacket Material	LSZH™/FRNC
Minimum Bend Radius	10 mm
Crush Resistance (reversible)	1000 N/10cm
Tensile strength	150 N

## Chemical characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

## Fibre Specifications

### Optical Characteristics (cabled)

Fibre Name	G50/125 ULTRA-BEND 7.5
Fibre Core Diameter	50 µm
Fibre Category	OM3
Fibre Code	H
Wavelengths	850 nm / 1300 nm
Maximum Attenuation	2.8 dB/km / 1.0 dB/km
Typical attenuation	2.4 dB/km / 0.8 dB/km

- Notes:
- 1) 50 µm multimode fibre macrobend loss ≤ 0.2 dB at 850 nm for two turns around 7.5 mm radius mandrel
  - 2) Meets 0.75 ns optical skew when used in all Corning Plug and Play™/Pretium EDGE® systems solutions.
  - 3) Improved attenuation and bandwidth options available
  - 4) Bend-insensitive single-mode fibres available on request
  - 5) Contact a Corning Customer Care Representative for additional information

# RFP LC Uniboot to RFP LC Uniboot Patch cord, 2 fibres, Interconnect tight-buffered cable, LSZH

50 µm ClearCurve® multimode OM3, Low-Loss, 2 m

CORNING

## Fibre Specifications

Optical Characteristics (cabled)	
Serial 1 Gigabit Ethernet	1000 m / 600 m
Serial 10 Gigabit Ethernet	300 m / 333 m
Min. Overfilled Launch (OFL) Bandwidth	1500 MHz*km / 500 MHz*km
Minimum Effective Modal Bandwidth (EMB)	2000 MHz*km / -
Induced attenuation @ 7.5 mm radius	< 0.2 dB / -

Notes: 1) 50 µm multimode fibre macrobend loss ≤ 0.2 dB at 850 nm for two turns around 7.5 mm radius mandrel  
2) Meets 0.75 ns optical skew when used in all Corning Plug and Play™/Pretium EDGE® systems solutions.  
3) Improved attenuation and bandwidth options available  
4) Bend-insensitive single-mode fibres available on request  
5) Contact a Corning Customer Care Representative for additional information

## Ordering Information

Part Number	E797902TNZ20002M
Product Description	Pretium EDGE® Solutions Low-loss Patchcord, LC duplex uniboot connectors, ClearCurve® Multimode 50/125 µm OM3 Pretium 300 fibres, standard reverse fibre polarity, LSZH/FRNC jacket, aqua, 2 m
EAN Code	4042673326861
Length	2 m
Weight	0.0142 kg

## Shipping Information

Packing type	Cardboard box
Packing dimensions (L x W x H)	380 mm x 250 mm x 180 mm
Units per Delivery	1/1



Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY  
00 800 2676 4641 · FAX: +49 30 5303 2335 · [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/emea/trademarks](http://www.corning.com/opcomm/emea/trademarks). Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2014 Corning Optical Communications. All rights reserved.