

# WCHE Housing

4 CCHE Panel capacity

CORNING

Corning wall-mountable connector housings provide interconnect or cross-connect capabilities between the outside plant, riser, or distribution cables and the opto-electronics.

The units can be wall-mounted in main cross-connect or telecommunication rooms, and are available in different versions with different capacities: 2 CCHE panels, 4 CCHE panels, 6 CCHE panels and 12 CCHE panels. All versions provide separate access to provider's and user's areas. Optional accessories such as the wall-mountable jumper storage guide kit (WJG-02R) and cable strain relief kit (WCH-STRNRLF-KIT) have been designed to make your wall-mountable product installation easier. The standoff bracket (WCH-STDOFF-BKT) is designed to extend the WCHE housing from the wall so that the cables can be routed behind the units. Brackets can be stacked to allow a larger space behind the units.

## Features and Benefits

Optimised design for field connectorization

Suitable for loose tube, tight buffered and ribbon fibre optic cables

Metal housing construction

Jumper routing guides and jumper strain relief points

Optional field-installable lock kit (for central door only)

Include bracket for buffer tube fan-out kits

Optional pivoting splice tray holders (to be ordered separately) allow easy cable routing and is designed to make field splicing easier. Splice trays must be ordered separately

Accept standard CCHE connector panels (to be ordered separately). CCHE panels are available for 6, 8, 12, 16\*, 24\* and 72\*\* fibre terminations for most commonly used connector types

-04P, -06P and -12P housings have a durable, clear polycarbonate-tinted jumper door for easy viewing of jumper connections

\* 16 and 24 fibre configurations are available only with LC duplex and MT-RJ adapters



Part Number: WCHE-04P



Part Number: WCHE-04P

# WCHE Housing

4 CCHE Panel capacity

CORNING

## Specifications

General Specifications	
Application	field connectorization
Mounting type	Wall-mount
Access type	Front access fixed
Lockable	yes, front side

Design - Hardware	
Housing material	Metal
Housing Colour	black
Cable entry type	grommeted slot

Mechanical Characteristics	
Dimensions (HxWxD)	343 mm x 408 mm x 103 mm
Weight	4.9 kg

## Ordering Information

Part Number	WCHE-04P
Product Description	WCHE Housing, black, 4 CCHE Panel capacity
EAN Code	4042673696506

## Shipping Information

Packing dimensions (L x W x H)	630 mm x 400 mm x 220 mm
Shipping Weight	6.3 kg
Units Per Delivery	1/1



Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY  
00 800 2676 4641 · FAX: +49 30 5303 2335 · [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/emea/trademarks](http://www.corning.com/opcomm/emea/trademarks). Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2016 Corning Optical Communications. All rights reserved.