

FutureCom™ EA CP Patch Cord, FRNC, S500 - RJ45

Grey, 15 m

CORNING

Plug and Play™ installation in Data Centre or in LANscape Consolidation Point Housings.

The FutureCom™ S500 consolidation point cable has four individual foil-shielded pairs (PiMF) and an additional braid shield (S/FTP). It is assembled with one shielded RJ45 connector in compliance with IEC 60603-7 and one S500^{FX} module. The FutureCom™ S500 consolidation point cable offers high margins for transmission of digital data signals for future applications in systems up to 10GbE according to the new class E_A (ISO/IEC 11801 Amd 2: 2009) respectively Cat.6A (ANSI/TIA/EIA 568B.2-10), EN 50173 and IEC 60603-7-5 Ed. 1.0. It is also suitable for Power over Ethernet (PoE) applications in compliance with IEEE 802.3af (2003) and the new PoE Plus applications.

The zero halogen patch cords (LSZH) are non-corrosive according to IEC 60754-2 (FRNC) and EN 50267, low smoke according to IEC 61034 and EN 50268 and flame retardant according to IEC 60332-1, Category B and EN 50266-2-1.

They are available in different lengths.



Part Number: CCAAGB-F1072-A150-C0

Features

- Plug & Play™ Installation
- 100% factory-tested quality
- No wire map failure during installation
- Short installation time
- Consolidation Point patch cable specified up to 500 MHz in compliance with class E_A and IEEE 802.3an
- S/FTP flex cable, Category 7
- High-quality RJ45 connector for 10 GbE systems
- Connector boot with latch protection

FutureCom™ EA CP Patch Cord, FRNC, S500 - RJ45

Grey, 15 m

CORNING

Specifications

General Specifications	
Environment	Indoor
Cable Assembly Type	Preconnectorised Cables
Cable Type	S/FTP
Category	6 _A
Halogen-free	Yes

Temperature Range	
Installation and assembly	0 °C to 50 °C
Operation	-20 °C to 60 °C

Design - Connector A	
Connector Type	RJ45 - 8/8

Mechanical Specifications - Connector A	
Durability	750 Cycles

Design - Connector B	
Copper Connector Type - B	S500

Cable Design	
Min. Bend Radius Installation	40 mm
Min. Bend Radius Operation	18 mm
Outer jacket material	LSZH/FRNC
Outer diameter	5.8 mm
Outer jacket colour	Grey

FutureCom™ EA CP Patch Cord, FRNC, S500 - RJ45

Grey, 15 m

CORNING

Mechanical characteristics

Conductor insulation	Braided shield Individual pair shield (PiMF)
Copper conductor	AWG 26
Temperature range (installation)	0 °C to 50 °C
Operating temperature	-20 °C to 60 °C

Electrical characteristics (at 20°C)

Frequency [MHz]*	1	10	20	31.25	62.5	100	300	600
Attenuation according to standard [dB/100 m]*	2.9	8.5	12.1	15.2	21.7	27.8	50	73.3
NEXT according to standard [dB/100 m]*	80	80	80	80	75.1	72.4	65.3	60.8
ACR-N according to Standard [dB/100 m]*	77.1	71.5	67.9	64.8	53.4	44.6	15.3	-12.5
*	-	-	-	-	-	-	-	-

Chemical characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

Ordering Information

Part Number	CCAAGB-F1072-A150-C0
Product Description	FutureCom™ EA Consolidation Point Patch Cord, 1x, FRNC, both ends terminated, S500 module - RJ45 connector, gray, 15 m
Length	15 m
Weight	0.72 kg

Shipping Information

Units per Delivery	1/1
--------------------	-----

FutureCom™ EA CP Patch Cord, FRNC, S500 - RJ45

Grey, 15 m

The CORNING logo is a blue square with the word "CORNING" in white, uppercase, sans-serif font centered inside.

Notes



Corning Cable Systems GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, Germany

TEL: 00800-2676-4641 (00800-CORNING1) · FAX: +49-30-5303-2335 · www.corning.com/cablesystems/emea

A complete listing of the trademarks of Corning Cable Systems is available at www.corning.com/cablesystems/emea/trademarks. Corning Cable Systems is ISO 9001 certified. © 2012 Corning Cable Systems. All rights reserved.